




KK AC 350

Compact AC unit



Lensegata 12
8656 Mosjøen, Norway

Tel: +47 751 13 090
Fax: +47 751 13 091

www.mkk.ac
post@mkk.ac

Company no.
876 035 502 MVA/VAT

KK AC 350

Compact AC unit



KK AC 350 in brief

KK AC 350 is a compact, flexible and silent AC unit developed for demanding conditions where the ambient temperature is no higher than +60°C. The unit has a cooling capacity of approximately 3,5 kW.

KK AC 350 can be mounted on the top of, or on the side of a cabin/room. The outlets on top of the unit can easily be connected to isolated channels/flexible piping. It is also possible to mount additional silencing on the piping if deemed necessary.

KK AC 350 has a chassis made of AISI 316L, with evaporator and condenser in copper/copper with a stainless frame. The unit is very robust and has proved to operate well under aggressive environments for our military, and industrial customers.

The unit is available for customization and can be built according to the specifications of the customer.

Product data

Height:	715 mm
Width:	550 mm
Length:	750 mm
Weight	110 Kg

Chassis material	AISI 316
Cooling capacity (+5°C/+50°C)	3,5 kW
Max power consumption	3,3 kW
Refrigerant	R 134A
Fill amount	1600 gr
Thermostat	Electrical
Air flow	840 m3/h
Voltage system	1~220-240V50Hz/265V60Hz

